

COLOURS/ DESIGNS



APPLICATIONS

Ideal for lining ute decks, vans, trucks, work benches, factory floors

FEATURES

- Approx. 11mm thick
- Multipurpose safety matting on a roll
- Anti-slip textured top
- Heavy duty rubber construction
- Outdoor use







Slip Resistance

Drainage

Suitable for Wet Areas







Outdoor Use

Custom



PROPERTIES	MEAGUIDED QUADA OTERIOTIOS	VALUE	CTANDARD	
	MEASURED CHARACTERISTICS	VALUE	STANDARD	
MATERIAL				
	Polymer	Natural Rubber		
	Colour	Black		
	Standard Sizes (mm)	See page 2		
	Surface Finish	Raised waffle pattern with holes		
	Backing Finish	Waffle Pattern		
MECHANICAL				
	Hardness	50 Shore A		
	Specific Gravitiy	1.50gm/cm ³		
	Tensile Strength (min)	3 mpa		
TEMPERATURE				
	Temperature Range	-10°C to +70°C		
CHEMICAL RESISTANCE				
	Petrol & Oil			
	Ozone & Weather			
	Flame Resistance			
	Animal & Vegetable Oil			
	Wear Resistance			
	Acid Resistance			
	Alkali Resistance			
KEY:	POOR FAIR	EXCELLENT		





THICKNESS (MM)	WIDTH (MM)	LENGTH (M)	WEIGHT
11	1500	1.5	20kg
11	1500	9m	15kg/m
*Sizes vary ± 2%			

* GECKOTRED