COLOURS/ DESIGNS

- Any logo can be custom printed
- 42 colour options, see page 2.
- Can be PMS colour matched extra charge may apply

APPLICATIONS

Ideal for entrances, high traffic areas, lift doors, reception areas, lobbies hallways/ corridors, floor areas for messages and advertising, indoor use

FEATURES

- Approx. 8mm thick
- Completely launderable washable up to 45°C, tumble dry up to 80°C
- Excellent dirt-catching performance
- 30% more absorbent than other mats
- Nylon pile solution dyed colourfast
- 100% PVC free
- Nitrile rubber backed with non-skid grippers
- Low profile sits flat without curling
- Slip and trip resistant
- Light resistant and suitable for underfloor heating
- Anti-static



Slip Resistance



Entrance



Indoor Use



Hi Traffic



Custom



Launderable



Classification of flammability test



PROPERTIES	MEASURED CHARACTERISTICS	VALUE	STANDARD
MATERIAL			
	Polymer	100% nitrile rubber backing and 100% high-twist nylon surface	
	Colours	Custom colours, see page 2 for 42 colour options (Can be PMS colour matched, extra charge may apply)	
	Standard Sizes (mm)	850 x 600 1200 x 850 1450 x 850 1800 x 1200 2400 x 850 Any size available up to 1.8 x 7m	
	Pile Weight	660g	
	Total Weight	2.5kg/m2	
	Thickness	8mm	
	Surface Finish	Cut pile carpet	
	Backing Finish	Cleated	
MECHANICAL			
	Colour Fastness	Pass 🍼	AATCC 61
	Electostatic Propensity	Pass 🍼	AATCC 134
	Surface Flammability	Pass 🍼	ASTM D 2859
	High Traction	Pass 🍼	NFSI 101-C
TEMPERATURE			
	Temperature Range	Up to +80°C	
CHEMICAL RESISTANCE			
	Petrol & Oil		
	Ozone & Weather		
	Flame Resistance		
	Animal & Vegetable Oil		
	Wear Resistance		
	Acid Resistance		
	Alkali Resistance		
KEY:	POOR FAIR	EXCELLENT	



COLOURS/ DESIGNS

- Any logo can be custom printed
- 42 colour options, see page 2. *Can be PMS colour matched extra charge may apply*

42 COLOUR OPTIONS:

