SPEC SHEET

DECKTRED MATTING

COLOURS/ DESIGNS



APPLICATIONS Ideal for lining ute decks, vans, trucks, work benches, factory floors, boats

FEATURES

- Approx. 10mm thick
- Multipurpose safety matting on a roll
- Anti-slip textured top . Heavy duty rubber construction
- . Outdoor use







Outdoor Use



PROPERTIES	MEASURED CHARACTERISTICS	VALUE	STANDARD
MATERIAL			
	Polymer	Natural Rubber	
	Colour	Black	
	Standard Sizes (mm)	See page 2.	
	Surface Finish	Textured blocks with holes	
	Backing Finish	Cleated	
MECHANICAL			
	Hardness	50 Shore A	
	Specific Gravitiy	1.50gm/cm ³	
	Tensile Strength (min)	3 mpa	
TEMPERATURE			
	Temperature Range	-10°C to +70°C	
CHEMICAL RESIST	ANCE		
	Petrol & Oil		
	Ozone & Weather		
	Flame Resistance		
	Animal & Vegetable Oil		
	Wear Resistance		
	Acid Resistance		
	Alkali Resistance		
KEY:		EXCELLENT	



SPEC SHEET

DECKTRED MATTING CONT.

THICKNESS (MM)	WIDTH (MM)	ROLL LENGTH (M)	ROLL WEIGHT (KG/M)
10	1500	9	12
10	1800	10	15.2
*Sizes vary ± 2%			

