

# PROFLEX INSERTION

## COLOURS/ DESIGNS



Black

## APPLICATIONS

- Ideal for ute/van liner, mud guards, conveyors

## FEATURES

- Available in four thicknesses
- 1-ply cotton insertion
- Hard wearing - very durable
- Absorbs noise
- Can be cut to custom lengths
- Tear resistance
- Indoor/outdoor use



Outdoor Use



Custom



1 YEAR GUARANTEE

PROPERTIES	MEASURED CHARACTERISTICS	VALUE	STANDARD
<b>MATERIAL</b>			
	Polymer	Natural Rubber	
	Colour	Black	
	Insertion Material	Cotton 1 ply	
	Surface Finish	Smooth	
	Backing Finish	Smooth	
<b>MECHANICAL</b>			
	Hardness	60 Shore A	ASTM D 2240
	Specific Gravity	1.6gm/cm <sup>3</sup>	ASTM D 297
	Tensile Strength (min)	40kg/mpa	ASTM D 412
	Elongation (min)	200%	ASTM D 412
<b>TEMPERATURE</b>			
	Temperature Range	-30°C to + 70°C	
<b>CHEMICAL RESISTANCE</b>			
	Petrol & Oil	●	
	Ozone & Weather	●	
	Flame Resistance	●	
	Animal & Vegetable Oil	●	
	Wear Resistance	●	
	Acid Resistance	●	
	Alkali Resistance	●	
<b>PACKAGING</b>			
	Rolled on cardboard tube Ø 80mm. Wrapped in black polyethylene film.		

### KEY:



POOR



FAIR



EXCELLENT

**PROFLEX INSERTION CONT.**

THICKNESS (MM)	WIDTH (MM)	ROLL LENGTH (M)	ROLL WEIGHT (KG)
1.5	25	10	0.6
1.5	50	10	1.1
1.5	75	10	1.7
1.5	100	10	2.3
1.5	150	10	3.4
1.5	200	10	4.5
1.5	300	10	6.8
1.5	1200	10	27
3	25	10	1
3	50	10	2
3	75	10	3
3	100	10	4.2
3	150	10	6.3
3	200	10	8.3
3	300	10	12.5
3	1200	10	50
4.5	25	10	1.1
4.5	50	10	2.1
4.5	75	10	3.1
4.5	100	10	4.2
4.5	150	10	10.3
4.5	200	10	13.7
4.5	300	10	20.5
4.5	1200	10	82
6	25	10	2.3
6	50	10	4.6
6	75	10	6.9
6	100	10	9.2
6	150	10	13.8
6	200	10	18.3
6	300	10	27.5
6	1200	10	110

\*Sizes vary ± 2%