

PROFLEX INSERTION

COLOURS/ DESIGNS



Black

APPLICATIONS

- Ideal for ute/van liner, mud guards, conveyors

FEATURES

- Available in four thicknesses
- 1-ply cotton insertion
- Hard wearing - very durable
- Absorbs noise
- Can be cut to custom lengths
- Tear resistance
- Indoor/outdoor use



Outdoor Use



Custom



PROPERTIES	MEASURED CHARACTERISTICS	VALUE	STANDARD
MATERIAL			
	Polymer	Natural Rubber	
	Colour	Black	
	Insertion Material	Cotton 1 ply	
	Surface Finish	Smooth	
	Backing Finish	Smooth	
MECHANICAL			
	Hardness	60 Shore A	ASTM D 2240
	Specific Gravity	1.6gm/cm ³	ASTM D 297
	Tensile Strength (min)	40kg/mpa	ASTM D 412
	Elongation (min)	200%	ASTM D 412
TEMPERATURE			
	Temperature Range	-30°C to + 70°C	
CHEMICAL RESISTANCE			
	Petrol & Oil	●	
	Ozone & Weather	●	
	Flame Resistance	●	
	Animal & Vegetable Oil	●	
	Wear Resistance	●	
	Acid Resistance	●	
	Alkali Resistance	●	
PACKAGING			
	Rolled on cardboard tube Ø 80mm. Wrapped in black polyethylene film.		

KEY:



POOR



FAIR



EXCELLENT

