

# KLEEN SCRAPE PERSONALISED

Not only do the Kleen Scrape Personalised mats create a visually attractive and unique entrance, they protect floors against the damaging effects of dirt, grit and dust. In modern businesses today, image is vital. It must be professional, yet distinctive, and a mat featuring a company logo and/or other relevant design can help reinforce a corporate identity. The heavy and durable Kleen Scrape Personalised mats work wonders in environments where traction is essential. Constructed of 100% nitrile rubber for oil and chemical resistance. Moulded face cleats act as scrapers to remove heavy dirt and soil from shoes and provide an excellent anti-slip surface.

## COLOURS/ DESIGNS



## APPLICATIONS

- Ideal for food processing areas, kitchens, factories with chemicals, factories with oil based fluids, workstations, counters, entrances, floor areas for messages and advertising

## FEATURES

- Approx. 5mm thick
- 100% nitrile rubber
- Anti-fatigue properties
- Skid resistant rubber back
- Rubber foam construction for comfort
- Castellated pattern surface for better grip
- Grease and chemical resistant
- Light-resistant and suitable for underfloor heating
- Heavy duty rating
- 2 years guarantee
- Indoor/outdoor use



Slip Resistance



Oil Resistant



Anti Fatigue



Food Service



Indoor Use



Outdoor Use



Custom

3  
YEARS  
GUARANTEE

5MM

THICK

\*Guaranteed against failure from manufacturing defects

| PROPERTIES                 | MEASURED CHARACTERISTICS     | VALUE                                  | STANDARD    |
|----------------------------|------------------------------|--|-------------|
| <b>MATERIAL</b>            |                              |  |             |
|                            | Polymer                      | 100% Nitrile Rubber                    |             |
|                            | Colour                       | Custom                                 |             |
|                            | Standard Sizes (mm)          | 860 x 760<br>1400 x 860<br>1700 x 1200 |             |
|                            | Weight                       | 4.20kg/sqm                             |             |
|                            | Thickness (mm)               | Approx. 8mm                            |             |
|                            | Backing Finish               | Smooth                                 |             |
| <b>MECHANICAL</b>          |                              |  |             |
|                            | Static electrical propensity | Antistatic                             | EN 14041    |
| <b>TEMPERATURE</b>         |                              |  |             |
|                            | Temperature Range            | -30°C to +60°C                         |             |
| <b>CHEMICAL RESISTANCE</b> |                              |  |             |
|                            | Petrol & Oil                 | ●                                      |             |
|                            | Ozone & Weather              | ●                                      |             |
|                            | Flame Resistance             | ●                                      |             |
|                            | Animal & Vegetable Oil       | ●                                      |             |
|                            | Wear Resistance              | ●                                      |             |
|                            | Acid Resistance              | ●                                      |             |
|                            | Alkali Resistance            | ●                                      |             |
| <b>KEY:</b>                |                              |  |             |
|                            | ● POOR                       | ● FAIR                                 | ● EXCELLENT |



**GECKOTRED**  
FLOOR SAFETY SOLUTIONS