

MULTIPRO COMFORT TILES

COLOURS/ DESIGNS



Closed - Solid Top



Open - With Holes

APPLICATIONS

- Ideal for food areas, around machinery, packing areas, wet areas, playgrounds

FEATURES

- Approx. 24mm thick
- Ergonomic and anti-fatigue
- Modular design, interlocking to cover large areas
- Available with and without holes
- Strong and robust
- Edge ramps available to eliminate tripping hazards
- Excellent sound dampening
- Made from recycled material
- UV protected
- Indoor/outdoor use



Slip Resistance



Anti Fatigue



Enviro Friendly



Modular



Drainage



Suitable for Wet Areas



Outdoor Use



Indoor Use



24mm THICK



6 YEARS GUARANTEE

| PROPERTIES | MEASURED CHARACTERISTICS | VALUE | STANDARD |
|----------------------------|--------------------------|--|-------------|
| MATERIAL | | | |
| | Polymer | PVC | |
| | Colour | Black | |
| | Standard Sizes (mm) | 500 x 500 | |
| | Thickness (mm) | 24 | |
| | Weight (kg) | 3.50 - Closed 2.78 - Open | |
| | Surface Finish | Textured solid top (Closed), Textured with holes (Open) | |
| | Backing Finish | Cleated | |
| MECHANICAL | | | |
| | Hardness | 78 Shore | |
| | ADA Compliance | Yes | |
| | Co-Efficient of Friction | Wet - 34-35 Dry - 90-92 | |
| | Fire Exposure | Passed | |
| | UV Stabilised | Yes | |
| TEMPERATURE | | | |
| | Temperature Range | -30°C to +60°C | |
| CHEMICAL RESISTANCE | | | |
| | Petrol & Oil | ● | |
| | Ozone & Weather | ● | |
| | Flame Resistance | ● | |
| | Animal & Vegetable Oil | ● | |
| | Wear Resistance | ● | |
| | Acid Resistance | ● | |
| | Alkali Resistance | ● | |
| KEY: | | | |
| | ● POOR | ● FAIR | ● EXCELLENT |

*Guaranteed against failure from manufacturing defects