

MULTIPRO ERGO TILES

COLOURS/ DESIGNS



Closed -
Solid Top



Open -
With Holes

APPLICATIONS

- Ideal for food areas, wet areas, swimming pools, playgrounds

FEATURES

- Approx. 14mm thick
- Excellent ergonomic qualities
- Modular design, interlocking to cover large areas
- Anti-slip tread on the top
- Available with or without holes
- Low profile, ramps available to eliminate tripping hazards
- Available in a selection of colours - please inquire
- Made from recycled material
- UV protected
- Indoor/outdoor use



Slip Resistance



Anti Fatigue



Enviro Friendly



Modular



Drainage



Suitable for
Wet Areas



Outdoor Use



Indoor Use



14mm
THICK



| PROPERTIES | MEASURED CHARACTERISTICS | VALUE | STANDARD |
|---|--------------------------|--|----------|
| MATERIAL | | | |
| | Polymer | PVC | |
| | Colour | Black | |
| | Standard Sizes (mm) | 500 x 250 | |
| | Thickness (mm) | 14 | |
| | Weight (kg) | - Closed - Open | |
| | Surface Finish | Textured solid top (Closed), Textured with holes (Open) | |
| | Backing Finish | Cleated | |
| MECHANICAL | | | |
| | Hardness | Shore | |
| | ADA Compliance | Yes | |
| | Co-Efficient of Friction | Wet - 69 Dry - 92-96 | |
| | Fire Exposure | Passed | |
| | UV Stabilised | Yes | |
| TEMPERATURE | | | |
| | Temperature Range | -30°C to +60°C | |
| CHEMICAL RESISTANCE | | | |
| | Petrol & Oil | EXCELLENT | |
| | Ozone & Weather | EXCELLENT | |
| | Flame Resistance | POOR | |
| | Animal & Vegetable Oil | EXCELLENT | |
| | Wear Resistance | EXCELLENT | |
| | Acid Resistance | EXCELLENT | |
| | Alkali Resistance | EXCELLENT | |
| KEY: ● POOR ● FAIR ● EXCELLENT | | | |

*Guaranteed against failure from manufacturing defects