

# PROFLEX EPDM

## COLOURS/ DESIGNS



Black

## APPLICATIONS

- Ideal for boats, ramps, chillers

## FEATURES

- Available in four thicknesses
- UV stabilised
- Marine grade
- Can be cut to custom lengths
- Indoor/outdoor use



Outdoor Use



Suitable for Wet Areas



Custom



PROPERTIES	MEASURED CHARACTERISTICS	VALUE	STANDARD
<b>MATERIAL</b>			
	Polymer	EPDM Rubber	
	Colour	Black	
	Insertion Material	-	
	Surface Finish	Smooth	
	Backing Finish	Smooth	
<b>MECHANICAL</b>			
	Hardness	60 Shore A	ASTM D 2240
	Specific Gravity	1.5gm/cm <sup>3</sup>	ASTM D 297
	Tensile Strength (min)	40kg/mpa	ASTM D 412
	Elongation (min)	180%	ASTM D 412
	Compression set after 24h at 70°C	50%	ASTM D395
<b>TEMPERATURE</b>			
	Temperature Range	-30°C to + 80°C	
<b>CHEMICAL RESISTANCE</b>			ASTM D 1149
	Petrol & Oil	●	
	Ozone & Weather	●	
	Flame Resistance	●	
	Animal & Vegetable Oil	●	
	Wear Resistance	●	
	Acid Resistance	●	
	Alkali Resistance	●	
<b>PACKAGING</b>			
Rolled on cardboard tube Ø 80mm. Wrapped in black polyethylene film.			
<b>KEY:</b>	● POOR	● FAIR	● EXCELLENT

# PROFLEX EPDM CONT.

THICKNESS (MM)	WIDTH (MM)	ROLL LENGTH (M)	ROLL WEIGHT (KG)
1.5	25	10	0.6
1.5	50	10	1.2
1.5	75	10	1.7
1.5	100	10	2.3
1.5	150	10	3.5
1.5	200	10	4.5
1.5	300	10	7
1.5	1200	10	28
3	25	10	1.2
3	50	10	2.4
3	75	10	3.5
3	100	10	4.8
3	150	10	7
3	200	10	9.5
3	300	10	14.3
3	1200	10	57
4.5	25	10	1.8
4.5	50	10	3.6
4.5	75	10	5.4
4.5	100	10	7
4.5	150	10	10.7
4.5	200	10	14.3
4.5	300	10	21.4
4.5	1200	10	86
6	25	10	2.4
6	50	10	4.8
6	75	10	7.2
6	100	10	9.6
6	150	10	14.4
6	200	10	19.2
6	300	10	28.8
6	1200	10	115

\*Sizes vary ± 2%