DIY JAZ GARAGE CARPET KIT

INSTRUCTIONS:

For best results, read through all the instructions first before you start.

1. What you are going to need: Garage Carpet, glue, trowel, knife provided in the kit, plus also a straight edge & tape measure.

2. Prepare the area; sweep & vacuum the garage to start with a clean surface.

3. Unroll carpet and lay out flat, may need to let it acclimatise so it isn't so rippled and easier to work with.

4. Measure the garage floor area. The carpet rolls are 2m wide x 6m-6.5m in lenth. Position the rolls in place on the floor, making sure they overlap by 50mm.

5. Roll up carpet to expose half the floor for gluing.

6. Spread glue evenly using the trowel provided (insure spread evenly for best result). Wait 20mins for glue to become tacty.

7. Unroll the carpet back onto the glued area and press the carpet down to the ground. Leave it for 30min.

8. While you are waiting you can double cut on the 50mm overlap join using a straight edge and knife. Pull the offcuts off both pieces of carpet to make the perfect join.

9. Trim the carpet down to fit around the outside wall and garage door edges.

10. After 30 min of leaving the glued carpet, press it again to get rid of any air bubles/ ripples.

11. Repeat steps 5 - 10 for the other half of the carpet.

Now the Garage Carpet installation is complete!

GECKOTRED
FLOOR SAFETY SOLUTIONS

0800 12 11 78 | sales@geckotred.com | www.geckotred.com